

Appendix D. Dose Calculations

Table of Contents

D.0	Dose Calculations	2
D.1	Supporting Information for Calculation of Public Doses	2
	D.1.1 Maximally Exposed Individual Dose.....	4
	D.1.2 Fifty-Mile (Eighty-Kilometer) Collective Population Dose	13
D.2	Calculation of Biota Doses	14
D.3	References	20

Tables

Table D-1.	Liquid Effluent Radionuclide Releases for GENII Dose Calculations.....	8
Table D-2.	Air Pathway Radionuclide Stack Emissions for GENII Modeling. (2 Pages)	9
Table D-3.	Agricultural Pathway Parameters for Hanford Site Dose Calculations.....	11
Table D-4.	Consumption Parameters for Hanford Site Dose Calculations.....	12
Table D-5.	Residency Parameters for Hanford Site Dose Calculations.	12
Table D-6.	Columbia River Parameters for Hanford Site Dose Calculations.....	12
Table D-7.	Biota Concentration Guides and Sediment to Water Distribution Coefficients.....	15
Table D-8.	Tier 1 Soil Biota Concentration Guides.....	15
Table D-9.	Maximum Detected Concentrations Evaluated for Aquatic Biota Dose Assessment.	16
Table D-10.	West Lake 2016 Water Samples.	17
Table D-11.	Tier 3 Biota Concentration Guides Calculated using RESRAD-BIOTA v1.8.	18
Table D-12.	Maximum Detected Concentrations Evaluated for Terrestrial Biota Dose Assessment	19

D.0 Dose Calculations

R Perona, RT Ryti, AG Fleury

Dose calculations based on measured and/or estimated releases from stack emissions, liquid effluents, and contaminated soils were conducted for the public and biota. These dose calculations are summarized in Section 4.2. Details of the methods and assumptions used for modeling individual and population dose for the public are provided in Section D.1. Methods and assumptions related to the calculation of biota dose are provided in Section D.2.

The total annual dose to a hypothetical, maximally exposed individual (MEI) in 2016 at the offsite location where projected doses were highest (Horn Rapids Road) was 0.12 mrem (1.2 μ Sv). This dose is 0.12% of the 100 mrem (1000 μ Sv) per year public dose limit specified in [DOE O 458.1, Radiation Protection of the Public and the Environment](#). For context, a 2009 National Council on Radiation Protection and Measurements report estimated that the overall annual exposure to ionizing radiation for the average American is 620 mrem (6,200 μ Sv), approximately half of which is related to natural sources and the other half attributable primarily to medical procedures.

D.1 Supporting Information for Calculation of Public Doses

The radiological dose that the public could have received in 2016 from the Hanford Site was calculated in terms of the *total effective dose*. The total effective dose is the sum of the effective dose equivalent from external sources and the committed effective dose equivalent for internal exposure, which are summarized here and described in more detail in [10 CFR 835, "Occupational Radiation Protection Program."](#) The committed effective dose equivalent is the sum of doses to organs and tissues that is weighted to account for the sensitivity of the organ or tissue to the effects of radiation and for the biological effectiveness of the type of radiation causing the dose. It is expressed in units of rem (Sv), or more typically the sub-unit mrem (mSv)² for individuals, and in units of person-rem (person-Sv) for the collective dose received by the total population within a 50-mi (80-km) radius of Hanford Site operations areas. This appendix describes how the doses summarized in Section 4.2 of this report were calculated.

Calculation of the total effective dose accounts for the long-term (50 yrs) internal exposure from radionuclides absorbed into the body during the current year. The committed effective dose equivalent is the sum of individual committed (50 yrs) organ doses multiplied by tissue weighting factors (ICRP 1991) that represent the contribution of each organ or tissue to a person's internal radiation dose. Internal organs also may be irradiated from external sources of radiation. The external exposure received during the current year is added to the committed internal dose to obtain the total effective dose.

Releases of radionuclides from Hanford Site facilities are frequently too small for their concentrations to be accurately measured in many of the offsite environmental media of interest. Even when present in measureable amounts, it can be difficult to distinguish the small Hanford Site contributions from levels attributable to fallout from historical nuclear weapons testing and from naturally occurring radionuclides such as uranium and its decay products. Therefore, Hanford-related environmental radionuclide concentrations were estimated from stack effluent measurements (air pathway doses) or

² 1 rem (0.01 Sv) = 1,000 mrem (10 mSv).

river water measurements (water pathway doses) by using environmental transport models. The air dose calculations employ environmental transport modeling based on measurements made at the points of release (stacks and vents). The water pathway dose calculations are based on the difference in measurements of radionuclide concentrations in the Columbia River upstream and downstream of the Hanford Site.

The transport of radionuclides in the environment to points of exposure is predicted using mathematical models of the physical processes underlying the various exposure pathways. These models are used to calculate radionuclide levels in air, soil, and foods at offsite locations. Long-lived radionuclides deposited on the ground by irrigation or airborne depositions become possible sources of external exposure and uptake by agricultural products. Radionuclides taken into the body by inhalation or ingestion may be distributed among different organs and tissues and retained in the body for various lengths of times. Agricultural, behavioral, and dosimetric models were applied to calculate radionuclide intakes and radiological doses to the public from annual-average radionuclide concentrations in the exposure media. Computer programs were used to implement these mathematical models using Hanford Site-specific dispersion and uptake parameters. These programs are incorporated in a master code, *GENII - The Hanford Environmental Radiation Dosimetry Software System, Version 2.10.1* (PNNL-14583; PNNL-14584; PNNL-19168), which employs the internal dosimetry methodology described in ICRP 60 (ICRP 1991) and external dose coefficients described in Federal Guidance Report 12 (EPA 1993). GENII Version 1.485 (PNL-6584), which incorporated internal dosimetry methods of *International Commission on Radiological Protection Publication 30* (ICRP 1979a and 1979b) was used for dose calculations through 2008. GENII Version 2.10 is a Microsoft Windows®-based version that also incorporates some environmental modeling improvements (e.g., plume depletion during atmospheric transport) relative to Version 1.485. GENII Version 2.10.1 was used for dose calculations starting with 2016 data. The modeling assumptions and radionuclide release data used in the GENII calculations are the primary focus of Section D.1. The ingestion and inhalation dose coefficients (ICRP 1991) and external dose coefficients (EPA 1993) used for the pathway dose calculations are described further in PNNL-14584 and are not reproduced here.

In addition to the GENII calculations for assessing public doses, the computer program CAP-88PC (also known as CAP-88) was used to calculate an air pathway dose to an MEI for compliance with [Clean Air Act of 1963](#) standards, as required by the U.S. Environmental Protection Agency (EPA) through [40 CFR 61, "National Emission Standards for Hazardous Air Pollutants,"](#) Subpart H, from airborne radionuclide effluents (other than radon) released at the U.S. Department of Energy (DOE) facilities. Air pathway calculations performed with the CAP-88PC computer code differ slightly from those performed in GENII. Technical details of the CAP-88PC calculations are provided in [DOE/RL-2017-17, Radionuclide Air Emissions Report for the Hanford Site, Calendar Year 2016](#).

Calculations of radiological doses to the public from radionuclides released into the environment are performed to demonstrate compliance with applicable standards and regulations. DOE O 458.1 provides requirements for demonstrating compliance with the public dose limit of 100-mrem (1,000- μ Sv) total effective dose in a year. Relevant requirements include the following:

- Compliance may be demonstrated by calculating dose to the representative person or to the MEI
- Collective dose for members of the public should be calculated, and may be truncated, by distance (e.g., 50 mi [80 km])

- The representative person or MEI must include members of the public outside of controlled areas on DOE sites and offsite
- Analytical models used to calculate dose must be codified or approved by DOE and must consider likely exposure pathways, including external radiation from air and soil, inhalation, and ingestion of water and terrestrial and/or aquatic foods
- Calculations of doses to the public from exposures resulting from both routine and unplanned activities must be performed using DOE-approved dose conversion factors
- Values of default or site-specific parameters used in the dose modeling must be included to document the calculations.

A summary of how the location of the offsite MEI was identified, and information on modeling assumptions and inputs to the GENII computer code used to conduct the MEI dose calculations is provided in Section D.1.1. Information supporting the calculation of collective offsite dose for members of the public using the GENII computer code is provided in Section D.1.2.

D.1.1 Maximally Exposed Individual Dose

The MEI is a hypothetical member of the public whose location and lifestyle make it unlikely that any actual individuals would receive higher doses. The location of the MEI can vary annually depending on the following:

- The relative contributions of the different operational areas to radioactive emissions released to the air
- The contribution of radionuclide releases to the Columbia River from Hanford Site facilities
- Variable differences in meteorology affecting wind dispersion
- The following potentially significant exposure pathways are considered for identifying the location of this hypothetical individual and calculating radiation dose:
 - Inhalation of airborne radionuclides
 - External exposure from submersion in airborne radionuclides
 - Ingestion of foodstuffs contaminated by radionuclides deposited on vegetation and the ground by airborne deposition and/or irrigation water drawn from the Columbia River downstream of the Hanford Site
 - Incidental ingestion of soil and external exposure to ground contaminated by airborne deposition and/or irrigation water
 - Ingestion of drinking water drawn from the Columbia River

-
- Consumption of fish from the Hanford Reach of the Columbia River
 - Recreational activities along the Hanford Reach of the Columbia River, including fishing, hunting, boating, swimming, and exposure to sediments during shoreline activities.

D.1.1.1 Determination of the Location of the MEI. Based on experience since 1990 from environmental transport modeling and environmental surveillance monitoring, four locations (Section 4, Figure 4.2) are considered for identifying the location of the MEI. The distinguishing characteristics of these locations are described in the following paragraphs.

Riverview MEI. The Riverview area is across the Columbia River from the City of Richland. Because of its location, an individual in the Riverview area has the potential to receive the maximum exposure to waterborne effluent from Hanford Site facilities as well as some contribution from exposure to airborne emissions from the 300 Area. The Riverview location is where a small population of West Pasco residents obtain their drinking water from the river via a community water system; therefore, the domestic drinking water pathway is applied to this location. Columbia River water from just downstream of the Hanford Site is also withdrawn for irrigation of small gardens and farms at Riverview.

Ringold MEI. The Ringold area is along the eastern shoreline of the Columbia River, 16 mi (26 km) east of separations facilities in the 200 Areas. Because of its location, an individual in the Ringold area has the potential to receive the maximum exposure to airborne emissions from the 200 Areas. In addition, it is assumed that some individuals in the Ringold area may irrigate their crops with water from the Columbia River downstream of where contaminated groundwater originating from the 100 and 200-East Areas enters the river. For identifying the MEI, Hanford Site contributions to irrigation water at Ringold are protectively evaluated using the same downstream concentrations employed for Riverview. Domestic drinking water at Ringold is not obtained from the Columbia River, so this exposure pathway is incomplete.

Sagemoor MEI. An individual in the Sagemoor area, located 0.87 mi (1.4 km) directly across the Columbia River from the 300 Area, frequently receives maximum exposure to airborne emissions from the 300 Area. However, domestic water at this location comes from wells rather than from the river; as a result, wells on the eastern side of the Columbia River are not impacted by radionuclides of Hanford Site origin. Because the farms located across from the 300 Area obtain irrigation water from the Columbia River upstream of the Hanford Site, irrigation-related exposure pathways are likely incomplete at this location. However, because some individuals may obtain much of their food from local agriculture, Columbia River irrigation pathways agricultural dose has been historically assigned to the Sagemoor area MEI. This practice protectively but unrealistically sums the location-specific air deposition component of food-related dose with the irrigation component from another location. The added contribution of radionuclides in the Riverview area irrigation water maximizes the calculated dose from the air and water pathways combined.

Horn Rapids Road MEI. Meteorological conditions in 2012 through 2016 resulted in a more southerly direction of wind dispersion than has been observed in past years. As a result, air concentrations related to 300 Area emissions were modeled to be slightly higher at a location just to the south of the Hanford Site boundary than at the Sagemoor location across the Columbia River to the east. Buildings in this area historically have been associated with commercial and industrial activities. However, in recent years, residences also have been constructed near the southern boundary of the Hanford Site south of the

300 Area. Residences in this area obtain drinking water from the City of Richland, which has an intake on the Columbia River downstream of the Hanford Site; therefore, the domestic drinking water pathway is applied to this location. Additionally, some agriculture in this area occurs on leased property that receives irrigation water from the Battelle pumping station on the Columbia River just below the 300 Area.

During the period of plutonium production at the Hanford Site, Ringold was commonly the location of the MEI. Because of the shift in Hanford Site operations from nuclear weapons production to the current mission of managing waste products, cleaning up legacy waste, and researching new ideas and technologies for waste disposal and cleanup, the significance of air emissions from production facilities in the 200 Areas has decreased compared to emissions from research facilities in the 300 Area. For the past two decades, the hypothetical MEI has been associated with air emissions from the 300 Area. Because the hypothetical MEI at all locations is assumed to potentially receive dose from consumption of foods raised using Columbia River irrigation water, the identification of the location of the MEI is based on the highest projected dose among the following air pathway receptor locations: at Ringold (200 Area sources), Sagemoor (300 Area sources), Horn Rapids Road (300 Area sources) plus drinking water pathway dose, and Riverview (300 Area sources) plus drinking water pathway dose.

For 2016, air pathway radiological dose calculations conducted using CAP-88PC in support of the *Clean Air Act of 1963* requirements and GENII Version 2.10.1 have identified the Horn Rapids Road as the location with the highest MEI dose. Air pathway calculations performed with the GENII computer code indicate that Sagemoor and Horn Rapids Road air pathway MEI doses in 2016 are similar (0.07 mrem at Sagemoor and 0.10 mrem at Horn Rapids Road). Unlike the Sagemoor receptor, the MEI at Horn Rapids Road receives additional dose from the drinking water pathway. Both Sagemoor and Horn Rapids Road MEI GENII results are shown in Section 4, Figure 4.4 for comparison.

MEI location coordinates relative to Hanford Site operating areas are entered in the GENII computer code to specify the location for the air pathway dose calculations. For Sagemoor, these coordinates are:

100 Area: 26.874 km Easting, 30.064 km Northing	300 Area: 1.35 km Easting, 0.26 km Northing
200 Areas: 24.954 km Easting, 20.814 km Northing	400 Area: 7.909 km Easting, 6.739 km Northing

For Horn Rapids Road, these coordinates are:

100 Area: 29.1 km Easting, -29.1 km Northing	300 Area: 0 km Easting, -1.80 km Northing
200 Areas: 22.6 km Easting, -22.6 km Northing	400 ea: 7.92 km Easting, -7.92 km Northing

D.1.1.2 Water and Air Release Inputs Used In GENII Version 2.10.1. As discussed in Section 4.2, the environmental data needed to perform the GENII dose calculations for the water pathway are differences in the measured upstream and downstream radionuclide concentrations in the Columbia River. The radionuclide releases to the Columbia River that are assumed to be the source of these differences are assigned to the 200 Areas, but area assignment does not affect the dose results. Measured emissions of radionuclides in stack releases are used in the GENII air pathway dose calculations. These air and water pathway data must be processed for input to the GENII computer code. GENII accepts inputs for environmental releases using dimensions of activity (e.g., curie or becquerel) per time for both water and air pathways.

Direct liquid effluent releases from outfalls in the 100 Area were historically used to characterize contributions from the 100 Area. The last operating outfall, 1908-K in the 100-K Area, ceased operations at the end of March 2011; therefore, no annual releases were identified from the 100 Area in 2016. Liquid effluent discharges related to historical Hanford operations are known to enter the Columbia River by groundwater discharge at certain locations along the site shoreline from the 100-B/C Area downstream to the 300 Area. The impact of these discharges was evaluated as the difference between near-shore riverwater radionuclide concentrations downstream of the Hanford Site (monthly samples collected at the Richland Pumphouse, sampling location label RICH.PMPHS HRM46.4) and upstream samples collected below the Priest Rapids Dam (monthly samples collected at sampling location label PRIEST RAPIDS-RIVER). Some radionuclides are measured in both filtered samples (in solution) and in samples that capture suspended particulates (adhered to resin). These data were evaluated both separately and summed.

One-tailed paired t-tests and nonparametric Wilcoxon Rank Sum (WRS) tests were used to determine whether average downstream sample concentrations were statistically greater than upstream average concentrations. The results of statistical tests were used in conjunction with supporting information such as known releases from groundwater plumes to the river and historical observations in river water to identify Hanford-related contaminants. The paired t-test is more powerful than the ordinary t-test when the values in the pairs correlate or when the concentrations measured downstream tend to correlate to those upstream. The WRS test has less power than the t-test when the data originate from a normal distribution, but the assumptions under which the statistical results are valid are not as restrictive. A p-value of 0.05 is commonly used as the threshold of statistical significance, but a larger, less restrictive value may be used when other factors support evidence of a release. Likewise, when a contaminant does not have any known Hanford Site sources, a smaller threshold could be appropriate to identify radionuclides for the dose assessment.

Both statistical tests identified tritium, uranium-234, and cobalt-60 as potentially Hanford-related contaminants to include in the 2016 water pathway dose assessment using a p-value of 0.05. Concentrations of uranium-238 were greater downstream, but p-values were slightly higher than 0.05 for both the t-test and WRS. Uranium-238 is retained as a potentially Hanford-related contaminant for the 2016 dose assessment because the higher downstream concentrations are considered plausibly site-related. Although uranium-235 might be expected to co-occur with both uranium-234 and uranium-238, yearly average uranium-235 concentrations were higher upstream than downstream and, therefore, uranium-235 is not included in the water pathway dose assessment calculations.

	p-value	
	paired t-test	Wilcoxon Rank Sum
Tritium	0.014	<0.077
Uranium-238	0.17	0.67
Uranium-234	0.0091	0.13
Cobalt-60 (resin)	0.042	0.78

Although statistical tests indicated cobalt-60 values were higher in downstream than upstream samples, cobalt-60 was not measured at levels above the minimal detectable activity in either the upstream or downstream samples. The significant p-values for both the t-test and WRS for cobalt-60 may have been biased due to the inclusion of calculations to normalize negative values as zeroes when summing the downstream filter and resin concentration values. Although cobalt-60 was not identified as a contaminant of potential concern (COPC) because it was not measured above the minimal detectable activity, water pathway calculations were run with cobalt-60 in order to determine whether it would be a significant contributor to dose. These results indicated cobalt-60 was a minor contributor to the irrigation, drinking water, and fish pathways compared to the other COPCs for both individual and population doses. Cobalt-60 would have contributed about 50% of the recreational pathway dose for both the individual and population doses, but the recreational dose makes up less than 1% of the total dose from the water pathway so its inclusion would not affect the overall water pathway results. Table D-1 summarizes the mean annual differences in downstream and upstream concentrations, and calculated annual releases for the 2016 GENII water pathway dose calculations.

Table D-15. Liquid Effluent Radionuclide Releases for GENII Dose Calculations.

Radionuclide	Upstream	Downstream	Difference
<i>Columbia River Annual-Average Radionuclide Concentrations (pCi/L)^a</i>			
Tritium	1.5E+01	2.3E+01	8.1E+00
Uranium-234	2.6E-01	2.9E-01	3.0E-02
Uranium-238	2.1E-01	2.2E-01	8.4E-03
<i>Calculated Radionuclide Releases (Ci/year)^b</i>			
Tritium	NA	NA	8.3E+02
Uranium-234	NA	NA	3.1E+00
Uranium-238	NA	NA	8.6E-01
Thorium-234 ^c	NA	NA	8.6E-01
Protactinium-234m ^c	NA	NA	8.6E-01

^a1 pCi=0.037 Bq

^b Calculated as the product of the difference in downstream and upstream radionuclide concentrations and the 2016 annual-average river flow rate of 3,239 m³/sec at Priest Rapids Dam and the number of seconds in a year.

^c These short-lived progeny of uranium-238 were protectively assumed to be in secular equilibrium at the time of discharge. Refer to Section 7.0 for information on Columbia River surfacewater sampling.

NA = not applicable; radionuclide releases calculated based on difference between annual-average downstream and upstream concentrations.

Radioactive air emissions based on monitoring of stacks in the 100, 200, 300, and 400 Areas were used as the basis for the GENII air pathway dose calculations. Stack emissions are measured for specific

radionuclides related to the operations at each emissions point. During the dispersion time from the stack to an offsite exposure location, there is opportunity for ingrowth of short-lived radioactive progeny that are included in the GENII radionuclide inventory. A protective upper-bound dispersion time of 15 hours was estimated based on the longest dispersion distance in the collective dose calculations (50 mi [80 km]) and an assumed (4.9 ft/sec [1.5 m/sec]) average wind speed. The highest short-term (15-hr ingrowth period) concentrations of short-lived progeny that have a separate dose conversion factor were included in the GENII air emissions inventory to address their potential contribution to the inhalation dose. Ingrowth of longer-lived progeny in soil and other environmental media is accounted for within GENII.

In addition to measurement of specific radionuclides, gross alpha and gross beta measurements are also made on emissions from each operating area. Following the precedent of DOE/RL-2017-17, measurements of gross alpha and gross beta radiation in stack emissions were protectively added to the measured emissions of plutonium-239/-240 and cesium-137, respectively, to ensure that contributions from any unmeasured operations-related radionuclides are incorporated in the estimated doses. These specific radionuclides were selected based on their historical association with releases in these operating areas and because air pathway calculations indicate dose is highest for these radionuclides among the group of plausible candidates of alpha- and beta-emitting radionuclides. Annual radionuclide air releases used in the GENII air pathway dose calculations are summarized in Table D-2.

Table D-16. Air Pathway Radionuclide Stack Emissions for GENII Modeling. (2 Pages)

Radionuclide	100 Area	200 Areas	300 Area	400 Area
	(Curies)			
Hydrogen-3 (elemental tritium)	NA	NA	23.9	NA
Hydrogen-3 (tritiated water vapor)	NA	NA	242	1.6E-02
Carbon-14	NA	NA	1.2E-04	NA
Sodium-22	NA	NA	NA	2.1E-10
Krypton-85	NA	NA	9.7E-08	NA
Stontium-90	3.2E-06	2.2E-05	1.7E-07	NA
<i>Yttrium-90^{a, b}</i>	4.8E-07	3.4E-06	2.5E-08	NA
Technetium-99	NA	NA	4.1E-06	NA
Ruthenium-106	NA	NA	1.3E-09	NA
Iodine-129	NA	9.8E-04	NA	NA
Cesium-134	NA	NA	NA	NA
Cesium-137 ^c	1.6E-05	7.0E-05	4.9E-06	1.9E-06
<i>Barium-137m^{a, b, c}</i>	1.6E-05	7.0E-05	4.9E-06	1.9E-06
Europium-152	NA	NA	1.9E-09	NA
Europium-154	NA	NA	1.1E-08	NA
Gadolinium-153	NA	NA	8.0E-11	NA
Radon-219	NA	NA	NA	
<i>Lead-211^{a, b}</i>	--	--	NA	
<i>Bismuth-211^{a, b}</i>	--	--	NA	
<i>Thallium-207^{a, b}</i>	--	--	NA	
Radon-220	NA	NA	178	NA
<i>Lead-212^{a, b}</i>	--	--	2.5E-01	NA
<i>Bismuth-212^{a, b}</i>	--	--	2.1E-01	NA
Radon-222	NA	NA	NA	NA
Radium-226	NA	NA	3.7E-10	NA

Table D-16. Air Pathway Radionuclide Stack Emissions for GENII Modeling. (2 Pages)

Radionuclide	100 Area	200 Areas	300 Area	400 Area
	(Curies)			
Actinium-227	NA	NA	3.1E-10	NA
Uranium-232	NA	NA	8.6E-09	NA
Uranium-233	NA	NA	2.7E-08	NA
Neptunium-237	NA	NA	1.4E-08	NA
Plutonium-238	5.0E-07	1.4E-07	3.7E-08	NA
Plutonium-239/240 ^d	1.3E-05	3.8E-05	1.1E-07	7.5E-07
Plutonium-241	8.8E-06	9.9E-08	NA	NA
Americium-241	2.7E-06	2.2E-06	4.8E-10	NA
Americium-243	NA	NA	4.9E-08	NA
<i>Neptunium-239^{a, b}</i>	--	--	8.2E-09	NA
(gross alpha)	1.0E-05	2.9E-05	1.0E-07	7.5E-07
(gross beta)	1.3E-05	6.3E-05	4.8E-06	1.9E-06

^a Radionuclides are short-lived progeny of the parent listed above that may ingrow during air dispersion to offsite locations.

^b Values of these short-lived progeny are the highest activity calculated within an estimated 15-hr dispersion time period to an exposure point within a 50-mi (80-km) distance.

^c Values include the addition of gross beta activity.

^d Values include the addition of gross alpha activity.

--

=

NA = Not available or not detected. No stack emissions reported for this radionuclide.

D.1.1.3 Exposure Parameter Values Used in GENII Version 2.10.1. GENII Version 2.10.1 requires input values for numerous parameters used in the environmental transport and human exposure models. Important parameters affecting the movement of radionuclides within agricultural exposure pathways such as animal dietary parameters, irrigation rates, crop yield, growing periods, and holdup periods are listed in Table D-3. The plant, animal, and aquatic foods transfer factors used for the pathway dose calculations are documented in PNNL-14584 and are not reproduced here.

The offsite radiological dose is related to the extent of external exposure to or intake of radionuclides released from Hanford Site operations that become incorporated in exposure media such as air, water, soil, sediment, and various foodstuffs. Tables D-4 through D-6 provide the values for the diet, residency, and river recreation parameters for the MEI and collective dose (average individual) calculations.

D.1.1.4 Meteorological Data Used in GENII Version 2.10.1. GENII Version 2.10.1 employs an atmospheric dispersion model to calculate annual-average air concentrations and deposition rates at downwind locations based on site-specific radionuclide air emissions measurements and meteorological data (PNNL-14583). The 2016 meteorological data used in the GENII air dispersion modeling were gathered at monitoring stations in the 100 Area (station 29 100-K; station 13 100-N), 200 Areas (station 21; Hanford Meteorological Station), 300 Area (Station 11; 300 Area), and 400 Area (station 9; Fast Flux Test Facility). With the exception of the 100 and 200 Areas, all meteorological data were obtained at a height of 33 ft (10 m). In the 100-K Area, a temporary tower was implemented at 10 ft (3 m) in height, the 100-K and 100-N Area meteorological data were combined for 2016 evaluation. In the 200 Areas, where some active stacks are 200 ft (61 m) in height, the meteorological data used were collected at 200 ft (61 m).

Table D-17. Agricultural Pathway Parameters for Hanford Site Dose Calculations.

Medium	Vegetables		Fruit s	Cerea ls	Eggs	Poultr y	Beef	Milk	Hay (beef catt le, milk cows)	Pastur e (milk cows)	Grains (beef cattle , poultry)
	Leafy	Root									
Holdup time ^a ; day (MEI)	1	5	5	180	1	1	15	1	100	0	180
Holdup time ^a ; day (population)	14	14	14	180	18	34	34	4	100	0	180
Growing period; day	90	90	90	90	NA	NA	NA	NA	45	30	90
Yield; kg/m ^b	1.5	4	2	0.8	NA	NA	NA	NA	2	1.5	0.8
Irrigation rate; cm/yr	77	88	77	^c	NA	NA	NA	NA	103	103	^c
Irrigation period; month	6	6	6	^c	NA	NA	NA	NA	6	6	^c
Water intake; L/year	NA	NA	NA	NA	0.3	0.3	50	60	NA	NA	NA
Food intake; kg/day	NA	NA	NA	NA	0.12	0.12	68/68 ^d	55/55 ^e	NA	NA	NA
Contaminated fraction of diet ^b	NA	NA	NA	NA	1.0	1.0	0.25/0.7 5 ^d	0.25/0.7 5 ^e	NA	NA	NA
Livestock soil intake; kg/day	NA	NA	NA	NA	0.0	0.0	0.0	0.375 ^f	NA	NA	NA

^a Holdup time is the time between harvest and consumption

^b Pertains to animal feed; 100% of animal water is assumed contaminated surfacewater.

^c No irrigation is assumed to occur for cereal crops or grains.

^d First value pertains to grains, and second value pertains to hay.

^e First value pertains to hay, and second value pertains to pasture grass.

^f Calculated as 0.5 kg soil/day while grazing × 0.75 diet fraction of pasture grass.

MEI=maximally exposed individual;

NA=not applicable

Table D-18. Consumption Parameters for Hanford Site Dose Calculations.

Medium	Consumption Rate ^a	
	Maximally Exposed Individual	Average Individual (Collective Dose)
Leafy vegetables	66 lbs (30 kg)/yr	33 lbs (15 kg)/yr
Root vegetables	485 lbs (220 kg)/yr	310 lbs (140 kg)/yr
Fruits	728 lbs (330 kg)/yr	140 lbs (64 kg)/yr
Cereals	180 lbs (80 kg)/yr	160 lbs (72 kg)/yr
Milk	71 gal (270 L)/yr	61 gal (230 L)/yr
Beef	180 lbs (80 kg)/yr	150 lbs (70 kg)/yr
Poultry	40 lbs (18 kg)/yr	19 lbs (8.5 kg)/yr
Eggs	66 lbs (30 kg)/yr	44 lbs (20 kg)/yr
Fish ^b	88 lbs (40 kg)/yr	-- ^c
Drinking water ^d	193 gal (730 L)/yr	116 gal (440 L)/yr
Inadvertent soil ingestion	1.17 oz (36.5 g)/yr	0.59 oz (18.3 g)/yr

^a A transit time of 11 hrs from the release to receptor locations is assumed.

^b A holdup time of 1 day is used for both MEI and population calculations.

^c Average individual consumption not identified; see text of Section D.1.2.

^d A holdup time of 1 day is used for the Riverview calculations for identification of the location of the MEI.

Table D-19. Residency Parameters for Hanford Site Dose Calculations.

Pathway	Exposure	
	Maximally Exposed Individual	Average Individual (Collective Dose)
Air: Inhalation ^{a, b}	24 hrs/day, 365 days/yr	24 hrs/day, 365 days/yr
Air: external (submersion) ^b	24 hrs/day, 365 days/yr	24 hrs/day, 365 days/yr
Soil: external (ground shine)	12 hrs/day, 365 days/yr	8 hrs/day, 365 days/yr

^a Inhalation rate, adult 1.0 m³/hr (35 ft³/hr).

^b Dispersion time of 15 hrs is protectively assumed for ingrowth of short-lived progeny during transport (50 mi [80 km]) population dose radius and 4.9 ft/s (1.5 m/s) wind speed.

Table D-20. Columbia River Parameters for Hanford Site Dose Calculations.

Activity and Pathway	Exposure ^a	
	Maximally Exposed Individual	Average Individual (Collective Dose)
Shoreline: sediment; external	5.0 hrs/day, 100 days/yr ^b	1.7 hrs/day, 10 days/yr ^b
Boating: river water; external	2.0 hrs/day, 50 days/yr ^c	0.1 hr/day, 50 days/yr ^c
Swimming: river water; inadvertent ingestion ^d , external	2.0 hrs/day, 50 days/yr	0.2 hr/day, 50 days/yr

^a A transit time of 11 hrs from the release to receptor locations is assumed.

^b A shoreline width factor of 0.2 is used.

^c No shielding by the boat is assumed.

^d Ingestion rate of 0.68 oz (0.02 L)/hr.

Because a large amount of data were missing for meteorological station 29 (100-K) and station 13 (100-N), the two data files were combined. The 100 Area air pathway doses were calculated using this combined data file.

Hourly meteorological data from the monitoring stations described above were formatted for use in the GENII computer code. Five meteorological files, one for each of the Hanford Site operating areas and stations described above, were created. These files were referenced in the GENII Chronic Plume Air Module. A radial grid consisting of 16 directional sectors and 10 downwind distances was specified in the air module. The downwind distances were varied for each operating area to coincide with the distance to the MEI location, as defined by the Easting and Northing coordinates described above. For example, the finest resolution was entered for the distance from the 300 Area to the MEI location

D.1.2 Fifty-Mile (Eighty-Kilometer) Collective Population Dose

Regulatory limits have not been established for collective doses to a population; however, evaluation of the collective population doses to all residents within a 50-mi (80-km) radius of Hanford Site operations is required by DOE O 458.1. The radiological dose received by the total population within 50 mi (80 km) of site operation areas was calculated to confirm adherence to DOE environmental protection policies, and provide information to the public. The 50-mi (80-km) collective dose is the sum of doses to all individual members of the public within 50 mi (80 km) of the four Hanford Site operations areas (100, 200, 300, and 400 Areas).

The same exposure pathways evaluated for the MEI (Section D.1.1) were used to calculate doses to the offsite population. The primary difference between the MEI and collective dose calculations is in the values selected for certain exposure parameters. As shown in Tables D-4, D-5, and D-6, exposure parameter values for the collective dose calculations reflect an average individual rather than an MEI.

In calculating the collective dose related to water-mediated exposure pathways (drinking water, irrigated foods, Columbia River recreation, and fish consumption), estimates were made of the offsite population size expected to be affected by each pathway. The assumptions of population size and the calculation of collective dose for each of these four exposure pathways are described in the following paragraphs.

D.1.2.1 Drinking Water. The Cities of Richland and Pasco obtain all or part of their municipal water directly from the Columbia River downstream from the Hanford Site; the City of Kennewick obtains its municipal water indirectly from wells adjacent to the river. Approximately 182,000 people residing in the Tri-Cities³ are assumed to obtain all of their drinking water directly from the Columbia River or from impacted wells near the river that are assumed to have the same radionuclide concentrations as were measured in near-shore river water. Annual drinking water dose for an average individual is multiplied by the Tri-Cities population to calculate the collective drinking water dose.

D.1.2.2 Irrigated Food. Columbia River water is withdrawn for irrigation of small vegetable gardens and farms in the Riverview area of Pasco in Franklin County. It is assumed enough food is grown in this area to feed an estimated 2,000 people. Commercial crops are also irrigated by the Columbia River in the Horn Rapids area of Benton County. Because these crops are widely distributed, any individual in the Tri-Cities is likely to receive only negligible potential exposure. An annual irrigated foods dose for an average individual is protectively multiplied by the estimate population of 2,000 individuals to calculate the collective irrigated foods dose.

³ The Cities of Pasco, Kennewick, and Richland—known as the Tri-Cities—are located in southeastern Washington State. Population estimates from <https://factfinder.census.gov/faces/nav/jsf/pages/index.xhtml>.

D.1.2.3 Columbia River Recreation. As described in Section 4.2 and Section D.1.1, recreational activities on the Columbia River include fishing, swimming, boating, and shoreline recreation. It was protectively assumed that all 182,000 individuals in the Tri-Cities participated in these recreational activities. Annual recreational dose for an average individual is multiplied by the Tri-Cities population to calculate the collective recreational dose.

D.1.2.4 Fish Consumption. Population doses from consuming fish obtained locally from the Columbia River were calculated from an estimated total annual catch of 33,000 lb (15,000 kg) per year. It was protectively assumed that 100% of the annual catch was consumed by individuals in the Tri-Cities area, and that tissue concentrations in the fish were in equilibrium with concentrations of radionuclides in river water (which is likely to introduce a protective bias for anadromous fish such as salmon and steelhead). Population dose related to fish consumption was calculated as follows:

Population dose (person-rem) = MEI dose (mrem) \times 0.001 rem/mrem \times (annual catch [kg/yr]/IR_fish [kg/yr/person]), where MEI dose=fish ingestion dose for the MEI; annual catch=15,000 kg fish/yr; IR_fish=individual fish ingestion rate used in the MEI calculation (40 kg/yr/person).

Collective dose related to air-mediated exposure pathways was calculated based on the geographic distribution of the population residing within a 50-mi (80-km) radius of the Hanford Site operating areas, as shown in [PNNL-20631, Hanford Site Regional Population—2010 Census](#). These distributions are based on 2010 United States Census Bureau data and influence the population dose by providing estimates of the number of people exposed to radioactive air emissions and their proximity to the points of release.

The air pathway collective dose calculations are based on modeled radionuclide air concentrations and deposition rates downwind of the Hanford Site operating areas coupled with the geographic population distribution in these areas. Both meteorological and population distribution data are organized according to 16 directional sectors based on the four cardinal, four ordinal, and eight cross-wind directions (e.g., N, NNE, NE, ENE). These sectors were transformed into grids using concentric circles with radii of 1, 2, 3, 4, 5, 10, 20, 30, 40, and 50 mi. These radii correspond to the downwind distances specified in the GENII Chronic Plume Air Module. Population files were created based on the number of individuals located in each of the 160-grid segments centered on the 100, 200, 300, and 400 Areas (PNNL-20631). These files were identified in the GENII Air Dose Report Module.

D.2 Calculation of Biota Doses

The RESidual RADioactivity (RESRAD)-BIOTA 1.8 computer code was used to screen the 2016 radionuclide concentrations in water, sediment, soil, and tissues to see if they exceeded the established biota concentration guides. Biota concentration guides are concentrations published in [DOE-STD-1153-2002, A Graded Approach for Evaluating Radiation Doses to Aquatic and Terrestrial Biota](#), that could result in a dose rate of 1 rad per day for aquatic biota or 0.1 rad per day for terrestrial organisms. Table D-7 presents water and sediment Tier 1 biota concentration guides for the radionuclides evaluated. Table D-8 presents the soil Tier 1 biota concentration guides for the radionuclides evaluated. Both internal and external doses to aquatic, riparian, and terrestrial animals and plants are included in the screening process. For with multiple media and radionuclides analyses, a sum of fractions is calculated to account for the contribution to dose from each radionuclide relative to its corresponding biota concentration guide. If the sum of fractions exceeds 1.0, then the dose guideline has been exceeded. If the initial estimated screening value (Tier 1) exceeds the dose limit (sum of fractions more

than 1.0), additional screening calculations are performed (Tiers 2 or 3) to evaluate accurate exposure of biota to radionuclides. The process may culminate in a site-specific assessment requiring additional sampling and study of exposure.

Table D-21. Biota Concentration Guides and Sediment to Water Distribution Coefficients.

Radionuclide	Water (pCi/L) ^a	Limiting Organism	Sediment (pCi/g) ^a	Limiting Organism	Default Kd (mL/g) ^b
Hydrogen-3	2.65E+08	Riparian animal	3.74E+05	Riparian animal	0.001
Carbon-14	6.09E+02	Riparian animal	5.90E+04	Riparian animal	0.001
Strontium-90	2.78E+02	Riparian animal	5.82E+02	Riparian animal	30
Technetium-99	6.67E+05	Riparian animal	4.22E+04	Riparian animal	5
Cesium-137	4.26E+01	Riparian animal	3.12E+03	Riparian animal	500
Plutonium-238	1.76E+02	Aquatic animal	5.73E+03	Riparian animal	2000
Plutonium-239/-240	1.87E+02	Aquatic animal	5.86E+03	Riparian animal	2000
Uranium-234	2.02E+02	Aquatic animal	5.27E+03	Riparian animal	50
Uranium-235	2.17E+02	Aquatic animal	3.73E+03	Riparian animal	50
Uranium-238	2.23E+02	Aquatic animal	2.49E+03	Riparian animal	50

^a 1 pCi=0.037 Bq. Biota concentration guides (pCi/g or pCi/L) from RESRAD-BIOTA v1.8.

^b Kd=Water to Sediment Distribution Coefficients (mL/g) from RESRAD-BIOTA v1.8.

RESRAD = RESidual RADioactivity

Table D-22. Tier 1 Soil Biota Concentration Guides.

Radionuclide	Soil (pCi/g) ^a	Limiting Organism
Strontium-90	2.25E+01	Terrestrial animal
Cesium-137	2.08E+01	Terrestrial animal
Plutonium-238	5.27E+03	Terrestrial animal
Plutonium-239/-240	6.11E+03	Terrestrial animal
Uranium-234	5.13E+03	Terrestrial animal
Uranium-235	2.77E+03	Terrestrial animal
Uranium-238	1.58E+03	Terrestrial animal
Americium-241	3.89E+03	Terrestrial animal

^a 1 pCi=0.037 Bq. Biota concentration guides (pCi/g) from RESRAD-BIOTA v1.8.

RESRAD = RESidual RADioactivity

In the initial (Tier 1) screening assessment, researchers compare maximum measured concentrations to the biota concentration guides. The maximum detected concentrations evaluated for aquatic biota dose assessment are presented in Table D-9. If the sum of fractions does not exceed one, no further analysis is required. However, if the sum of fractions does exceed one, a second analysis (Tier 2) is performed using average concentrations and the same Tier 1 biota concentration guides. For the aquatic biota dose assessment, paired sediment and water data are required. In the event that only one of these media was sampled, the other was calculated using an element-specific sediment to water distribution coefficient. These coefficients are tabulated in Table D-7.

The sites for the aquatic biota dose assessment were grouped into upstream (Vernita sediment and Priest Rapids Dam river water samples), the 100 Area (sediments from 100-K, 100-D, 100-H, 100-F and White Bluff; river water from 100-N; and seeps from 100-BC, 100-K, 100-N, 100-D, 100-H, 100-F), the Hanford Town Site (sediments from Hanford slough, Savage Island, and Locke Island; river water; and seep water from Hanford Spring); the 300 Area (river water and springs), and downstream (sediments from McNary Dam and river water from the Richland Pumphouse).

Table D-23. Maximum Detected Concentrations Evaluated for Aquatic Biota Dose Assessment.

Location Group	Radionuclide	Maximum Sediment (pCi/g) ^a	Maximum Water (pCi/L) ^a
Upstream	Hydrogen-3	—	26.8
	Cesium-137	0.296	—
	Plutonium-239/-240	0.0144	—
	Uranium-234	1.41	0.356
	Uranium-235	0.0937	0.0707
	Uranium-238	1.25	0.283
100 Area	Hydrogen-3	—	4000
	Carbon-14	—	302
	Strontium-90	—	51.9
	Cesium-137	0.288	—
	Plutonium-239/-240	0.00161	—
	Uranium-234	1.34	1.18
	Uranium-235	0.121	0.025
	Uranium-238	1.24	1.5
Hanford Townsite	Hydrogen-3	—	21200
	Cesium-137	0.219	—
	Uranium-234	1.13	0.279
	Uranium-235	0.111	0.0469
	Uranium-238	1.21	0.203
	300 Area	Hydrogen-3	—
Cesium-137		0.179	—
Uranium-234		3.07	23.9
Uranium-235		0.272	2.28
Uranium-238		2.89	25.7
Downstream	Hydrogen-3	—	49.6
	Cesium-137	0.223	—
	Plutonium-239/-240	0.0153	—
	Uranium-234	1.51	0.38
	Uranium-235	0.106	0.0732
	Uranium-238	1.22	0.311
^a 1 pCi = 0.037 Bq			
— = Not detected or not measured.			

Radionuclides were selected for the aquatic biota dose assessment based primarily on their detection in sediment or water. In addition, having known or suspected sources from DOE operations, the results for tissue samples compared to reference (i.e., upstream, generally at Vernita Bridge), and the known potential for bioaccumulation was also used to identify which radionuclides should be included in the dose assessment. Most of the detected radionuclides in water – hydrogen-3 (tritium), carbon-14, strontium-90, technetium-99, and isotopic uranium – could readily be associated with known groundwater plumes. Most of the remainder of the detected radionuclides could have sources from DOE operations; however, due to relatively high soil-water distribution coefficients, these radionuclides would most likely be associated with sediments instead of water. Cesium-137 and isotopic plutonium were detected in sediments and may have sources from DOE operations. Although the magnitude of the sediment concentrations onsite is sometimes no greater than upstream, these radionuclides are included in the aquatic biota dose assessment. This is likely protective, as these radionuclides are not elevated above reference in tissues. Potassium-40 has no groundwater plumes or other known DOE sources; therefore, potassium-40 was not included in the aquatic biota dose assessment.

As discussed in Section 4.2.6, biota doses were evaluated for Columbia River water and sediment and West Lake water, sediment, and soils (onsite and offsite). For West Lake, Tier 1 sum of fractions exceeded 1.0; therefore, Tiers 2 and 3 calculations were implemented using the mean water concentrations presented in Table D-10. The tiered screening process is further described in DOE-STD-1153-2002.

Table D-24. West Lake 2016 Water Samples.

Radionuclide	Water Concentration (pCi/L) ^a		Sediment Concentration (pCi/g) ^a	
	Maximum	Average	Maximum	Average
Strontium-90	—	—	0.44	0.313
Technetium-99	—	—	0.598	0.598
Cesium-137	—	—	1.38	0.821
Uranium-234	10700	3880	9.57	5.16
Uranium-235	43.5	25.9	0.647	0.402
Uranium-238	13700	4860	9.31	4.77

^a pCi=0.037 Bq

— = Not detected or not measured.

The Tier 1 and 2 West Lake biota dose assessments were driven by the potential for dose from uranium isotopes in water and the assumed potential for these isotopes to accumulate in biota. The isotopic ratios of uranium indicate a natural source (granitic erratic's from the Missoula floods) and no uranium-236 was detected, albeit some minor amounts of depleted uranium may be present (PNL-7662). Therefore, the Tier 3 West Lake biota dose calculations utilized site-specific information on bioaccumulation. As defined in DOE-STD-1153-2002, bioaccumulation is the ratio of the contaminant concentration in the organism relative to the contaminant concentration in an environmental medium resulting from the uptake of the contaminant from one or more routes of exposure. The more relevant biota data collected from West Lake are the brine flies sampled in 2000 and 2007 (PNNL-13487;

DOE/RL-2007-50). Birds (avocets) were also sampled in 2000 and had lower concentrations than the brine flies (PNNL-13487). These birds are not year-round residents and, thus, have lower exposure and less potential for bioaccumulation at West Lake (DOE/RL-2007-50, Appendix K).

The maximum concentration of any of the uranium isotopes in brine flies was 0.88 pCi/g for uranium-233/-234 in 2007. The minimum uranium-233/234 West Lake pond water concentration was 940 pCi/L in 2007. The bioaccumulation factor is calculated by dividing the biota concentration (in pCi/g) by the water concentration (in pCi/mL), because RESRAD-BIOTA assumes that aquatic bioaccumulation occurs from water to biota. Therefore, the maximum bioaccumulation factor for uranium would be less than one (0.88 divided by 0.94). Also, as presented in Table D-10 of the 2011 report ([DOE/RL-2011-119, Hanford Site Environmental Report for Calendar Year 2011](#)), bioaccumulation factors for uranium isotopes based on the mean concentrations in flies and water were between 0.2 and 0.5. A bioaccumulation factor of one was used for the West Lake Tier 3 biota dose calculation as a somewhat protective measure of site-specific uranium uptake into the food chain. This same approach was used in the 2011 (DOE/RL-2011-119) and 2012 ([DOE/RL-2013-18, Hanford Site Environmental Report for Calendar Year 2012](#)) reports. The data supporting the site-specific bioaccumulation factor are presented in those reports. Table D-11 presents the Tier 3 biota concentration guides for isotopic uranium for both aquatic and riparian animals. These site-specific values were used in the RESRAD-BIOTA Tier 3 screening discussed in Section 4.2.6.

Table D-25. Tier 3 Biota Concentration Guides Calculated using RESRAD-BIOTA v1.8.

Radionuclide	Water BCG (pCi/L) ^a		Sediment BCG (pCi/g) ^a	
	Aquatic Animal	Riparian Animal	Aquatic Animal	Riparian Animal
Uranium-234	202000	20200	3030000	5270
Uranium-235	217000	21700	110000	3790
Uranium-238	222000	22200	42900	2490

^a 1 pCi=0.037 Bq

RESRAD = RESidual RADioactivity

Dose to terrestrial biota were evaluated using the near-field and far-field soil sample results. Table D-12 lists the maximum concentrations of strontium-90, cesium-137, plutonium-238, plutonium-239/-240, uranium-234, uranium-235, and uranium-238. These radionuclides were selected for the terrestrial biota dose assessment based on their detection in soil. In addition, having known or suspected sources from DOE operations, vegetation sample compared to soil results and the known potential for bioaccumulation were used to include or exclude radionuclides for the biota dose assessment.

The biota dose assessment also included supplemental calculations using measured concentrations in tissues. Presented in Section 4.2.6, these supplemental calculations provide a more realistic estimate of biota dose compared to doses calculated using the protective bioaccumulation assumptions made in the Tier 1 dose assessments. Section 4.2.6 lists the detected tissue concentrations evaluated in these supplemental dose calculations. The tissue concentrations are used for the internal dose calculations, whereas external dose is estimated from the relevant soil, sediment, and water concentrations. Maxima were used in the supplemental internal dose calculations, which is more protective than the mean recommended by DOE guidance for these Tier 3 dose calculations. However, the detections were

infrequent for tissues and, therefore, the maximum detected values and mean detected values would be similar.

Table D-26. Maximum Detected Concentrations Evaluated for Terrestrial Biota Dose Assessment.

Location Group	Radionuclide	Maximum Soil (pCi/g) ^a
Near Field	Strontium-90	2
	Cesium-137	10
	Uranium-234	1.1
	Uranium-235	0.14
	Uranium-238	1.1
	Plutonium-238	0.0099
	Plutonium-239/240	0.69
	Americium-241	0.25

^a 1 pCi=0.037 Bq.

D.3 References

- 10 CFR 835, "Occupational Radiation Protection." *Code of Federal Regulations*, as amended. Online at <http://www.ecfr.gov/cgi-bin/text-idx?SID=40dc5b37cae52e891f095e943d5a3d69&mc=true&node=pt10.4.835&rgn=div5>.
- 40 CFR 61. "National Emission Standards for Hazardous Air Pollutants." *Code of Federal Regulations*, as amended. Online at http://www.ecfr.gov/cgi-bin/text-idx?tpl=/ecfrbrowse/Title40/40cfr61_main_02.tpl.
- Clean Air Act of 1963*. 42 U.S.C. 7401 et seq., Public Law 88-206, as amended. Online at <https://www.gpo.gov/fdsys/pkg/STATUTE-77/pdf/STATUTE-77-Pg392.pdf>.
- DOE O 458.1, Chg. 3. 2013. *Radiation Protection of the Public and the Environment*. U.S. Department of Energy, The Office of Environment, Safety and Health, Washington, D.C. Online at <https://www.directives.doe.gov/directives-documents/400-series/0458-1-border-admc3>.
- DOE/RL-2007-50. 2011. *Central Plateau Ecological Risk Assessment Data Package Report*. Rev. 1. U.S. Department of Energy, Richland Operations Office, Richland, Washington. Online at <http://pdw.hanford.gov/arpir/index.cfm/viewDoc?accession=1108100554>.
- DOE/RL-2011-119. 2012. *Hanford Site Environmental Report for Calendar Year 2011*. Rev. 0. U.S. Department of Energy, Richland Operations Office, Richland, Washington. Online at http://msa.hanford.gov/files.cfm/2011_DOE-RL_2011-119_HanfordSiteEnviroReport4CY2011.pdf.
- DOE/RL-2013-18. 2013. *Hanford Site Environmental Report for Calendar Year 2012*. Rev. 0. U.S. Department of Energy, Richland Operations Office, Richland, Washington. Online at http://msa.hanford.gov/files.cfm/2012_DOE-RL-2013-18_REV_0_cleared.pdf.

- DOE/RL-2017-17. *Radionuclide Air Emissions Report for the Hanford Site, Calendar Year 2016*. Rev. 0. U.S. Department of Energy, Richland Operations Office, Richland, Washington. Online at [http://www.hanford.gov/files.cfm/17-ESQ-0077 - Attachment.pdf](http://www.hanford.gov/files.cfm/17-ESQ-0077_-_Attachment.pdf).
- DOE-STD-1153-2002. *A Graded Approach for Evaluating Radiation Doses to Aquatic and Terrestrial Biota*. U.S. Department of Energy, Washington, D.C. Online at http://energy.gov/sites/prod/files/2013/09/f3/1153_Frontmatter.pdf.
- EPA. 1993. *External Exposure to Radionuclides in Air, Water, and Soil*. Federal Guidance Report No. 12, EPA-402-R-93-081. U.S. Environmental Protection Agency, Washington, D.C. Online at <https://nepis.epa.gov/Exe/ZyPDF.cgi/00000AA1.PDF?Dockey=00000AA1.PDF>.
- PNL-7662. 1991. *An Evaluation of the Chemical, Radiological, and Ecological Conditions of West Lake on the Hanford Site*. Pacific Northwest Laboratory, Richland, Washington.
- PNNL-13487. 2001. *Hanford Site Environmental Report for Calendar Year 2000*. Pacific Northwest National Laboratory, Richland, Washington. Online at https://msa.hanford.gov/files.cfm/PNNL-13487_2000.pdf.
- PNNL-14583. 2010. *GENIII Version 2 Users' Guide*. Rev 3. Pacific Northwest National Laboratory, Richland, WA. Online at http://www.pnnl.gov/main/publications/external/technical_reports/pnnl-14583rev3.pdf.
- PNNL-14584. 2011. *GENIII Version 2 Software Design Document*. Pacific Northwest National Laboratory, Richland, Washington. Online at http://www.pnnl.gov/main/publications/external/technical_reports/PNNL-14584Rev3.pdf.
- PNNL-19168. 2010. *Hanford Site Annual Report Radiological Dose Calculation Upgrade Evaluation*. Pacific Northwest National Laboratory, Richland, Washington. Online at http://www.pnl.gov/main/publications/external/technical_reports/PNNL-19168.pdf.
- PNNL-20631. 2011. *Hanford Site Regional Population—2010 Census*. Pacific Northwest National Laboratory, Richland, Washington. Online at http://www.pnnl.gov/main/publications/external/technical_reports/PNNL-20631.pdf.